



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY  
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY  
AND POLLUTION PREVENTION

May 10, 2018

Kevin Kutcel  
Agent for  
New Nautical Coatings, Inc.  
14805 49<sup>th</sup> St  
Clearwater, FL 33762

Subject: Notification per PRN 98-10 – Minor label modifications and new alternate brand names  
Product Name: Sea Hawk Premium Quality Cukote Anti-Fouling Coating  
EPA Registration Number: 44891-7  
Application Dates: March 9, 2018; April 9, 2018  
Decision Numbers: 539250, 540388

Dear Mr. Kutcel:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

The following alternate brand names have been added to the product record:

- Sea Hawk Cukote Anti-Fouling Coating
- Sea Hawk Yacht Finishes Premium Quality Cukote Anti-Fouling Coating
- Sea Hawk Premium Yacht Finishes Premium Quality Cukote Antifouling Coating

If you have any questions, you may contact Tara Flint via email at [flint.tara@epa.gov](mailto:flint.tara@epa.gov) or Eric Miederhoff at [Miederhoff.eric@epa.gov](mailto:Miederhoff.eric@epa.gov).

Sincerely,

A handwritten signature in blue ink that reads "E. Miederhoff". The signature is written in a cursive style with a large, stylized initial "E".

Eric Miederhoff  
Product Manager 31  
Regulatory Management Branch I  
Antimicrobials Division (7510P)  
Office of Pesticide Programs

Notes to reviewer are bracketed [ ]  
Statements in parenthesis are optional or alternative text ( )  
~~Strike through~~ Delete

**Highlighted**

[Brand Names]  
**Sea Hawk Premium Quality Cukote Anti-Fouling Coating**

[Alternative Brand Names]  
CUKOTE  
CUKOTE 330

Sea Hawk Cukote Anti-Fouling Coating  
Sea Hawk Yacht Finishes Premium Quality Cukote Anti-Fouling Coating  
Sea Hawk Premium Yacht Finishes Premium Quality Cukote Antifouling Coating

ACTIVE INGREDIENT:	
Cuprous Oxide (Cas NO. 1317-39-1).....	47.57%
OTHER INGREDIENTS:.....	52.43%
TOTAL .....	100.00%
Copper expressed as metallic 42.25%	
Contains Petroleum Distillates	
This product contains toxic inert ingredient propylene oxide.	

**KEEP OUT OF REACH OF CHILDREN**

**DANGER**  **POISON**

**SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS AND FIRST AID**

(**LIMITED WARRANTY:** The manufacturer warrants all material sold by it against defects in the material. The manufacturer's liability under the sale and warranty of this material shall in any case be limited to replacement of material only. The manufacturer makes no other warranty of this product, expressed or implied.)

**[OPTIONAL MARKETING STATEMENTS:]**

(Sea Hawk)  
(Yacht Finishes)  
(Premium Quality)  
(Antifouling Coating)  
(STANDARD FORMULATION)  
(330 VOC)  
(398 VOC)  
(Reduced VOC Formulation)  
(CA VOC Code Compliant)  
(California Compliant)  
(Tough on Barnacles)  
(Hand Crafted in America!<sup>SM</sup>)  
(Self Polishing)  
(Antifouling Paint)  
(Ablative)

**NOTIFICATION**

44891-7

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

05/10/2018

(Antifouling Bottom Paint)  
(330 grams/liter VOC)  
(Contains 330 grams/liter VOC)  
(VOC 330 grams/liter)  
(330 g/l VOC)  
(Contains 330 g/l VOC)  
(VOC 330 g/l)  
(Semi-hard, Self Polishing Ablative)  
(Multi-season Protection)  
(Cukote™)  
(Lloyd's Register Certified)  
(3430 Dark Blue)  
(3430-L Dark Blue)  
(3441 Red)  
(3441-L Red)  
(3442 Blue)  
(3442-L Blue)  
(3445 Black)  
(3445-L Black)  
(3433 Green)  
(3434 Teal)  
(3434-L Teal)  
(3432 Brown)  
(3432-L Brown)

[Optional Graphics]





**CUKOTE™**



Boost with  
Biocop TF

**PREMIUM QUALITY**



[ABOVE BAR CODE WILL APPEAR ON EACH CAN AND THE NUMBERS WILL CORRESPOND WITH THE BAR CODE ISSUED FOR THAT PRODUCT.]



[Above will be used with contents and manufacturer depending on the size]  
 [Net Contents:] (5-gallon pail 18.927 ), (Gallon 3.785 Liters), (Quart 0.9463 Liters)

(Batch Code) [to appear on front or back panel of the label or immediate container depending on the container type/size]

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**GENERAL DESCRIPTION**

Ablative, self-polishing antifoulant. This product controls barnacles, algae, and other marine organisms. It can be used in both fresh and salt water. This product has a copolymer, biocide release mechanism. The product prevents coating buildup and is able to be hauled for extended periods and then relaunched without affecting the antifouling properties.

**SHAKE VIGOROUSLY FOR A MINIMUM OF 10 MINUTES BEFORE APPLICATION**

*Note—Stirring with a Jiffy Mixer or paint paddle is not adequate.*

**PRODUCT INFORMATION**

**Finish/Sheen:** Semi-Gloss

**Copper Content:** 47%

**Mix Ratio:** One Pack

**Flash Point:** 100°F/38°C

**Converter:** One Pack

**Volume Solids:** 54% ± 2%

**Shipping Weight:** 18-20 Lbs./Gal.

**Theoretical Coverage:** 320 Sq. Ft./Gal. @ recommended film thickness

**APPLICATION DETAILS**

**APPLICATION:** Do not apply this product in a way that will contact adults, children, pets, either directly or through drift. Do not allow adults, children, or pets to enter the treated area until sprays have dried. Apply **at least** two coats by brush, roller or spray.

**Sweat-In Time:** Not Applicable **Cleaner:** Sea Hawk Xylene 7130

**Thinner:** Sea Hawk 2033-2035 for regular formulation. Sea Hawk 2053 for VOC 330 formulation.

**Overcoating Interval Drying Time (Hrs)**

Substrate Temp. Touch Min. Max. Launch

73°F (23°C) 2 Hrs 1 Hr N/A 12 Hrs

95°F (35°C) 1 Hr 1 Hr N/A 12 Hrs

Consult with your Sea Hawk representative for the system best suited for surfaces to be protected.

**REGULATORY DATA**

**VOC:** (398 Grams/Liter for standard formulation) (330 Grams/Liter Reduced VOC formulation)

**LIMITATIONS:** Apply in good weather when air and surface temperature are above 50°F (10°C). Surface temperature must be at least 5°F (1°C) above dew point. For optimum application properties, bring material to 70-80°F (21-27°C) temperature range prior to mixing and application. Unmixed material (in closed containers) should be maintained in protected storage between 40 and 100°F (4-38°C). Prolonged atmospheric exposure of this product may detract from performance. Technical and application data herein is for the purpose of establishing a general guideline for the coating and the proper coating application procedures. As application, environmental and design factors can vary significantly, due care should be exercised in the selection, verification of performance and use of the coating.

**SURFACE PREPARATION:** Paint only clean, dry surfaces. Remove all grease, oil, wax, or other foreign material by solvent or detergent washing. (SSPC-SPI)

**New Construction:** As yard procedures may vary, consult with your Sea Hawk Representative.

## EQUIPMENT

**Brush:** China Bristle

**Roller:** Solvent Resistant Roller Cover 3/8" pile smooth to medium. Prewash Roller Cover to remove loose fibers prior to use.

**Airless Spray:** Minimum 33:1-2 GPM ratio pump; "0.017-0.026" orifice tip; 3/8" ID high-pressure material hose; 90 PSI line pressure; 60 mesh filter.

**THINNING:** We do not recommend thinning. However, if thinning is necessary, thin up to a maximum of 10% with Sea Hawk 2033-2035 for VOC 398 formulation only. For VOC 330 formulation use Sea Hawk 2053 only.

**CLEANUP:** Clean all equipment immediately after use with Sea Hawk Xylene 7130. It is good practice to periodically flush out spray equipment during the course of the day. Frequency depends upon the amount sprayed, temperature, elapsed time including delay, etc.

**SAFETY:** Read and observe all precautionary statements on this label.

### STORAGE AND DISPOSAL

Do not contaminate food, feed or water by storage or disposal.

**Storage:** Do not store near heat or open flame. Store below 100°F/38°C. Store in well-ventilated area.

**Pesticide Disposal:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by the use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**Container Disposal:** Non-refillable container. Do not reuse or refill this container. Prior to container disposal, allow any remaining paint residue in the container to air dry. Dispose of the container in accordance with Federal, State or local disposal regulations.

### PRECAUTIONARY STATEMENTS

#### HAZARDS TO HUMANS AND DOMESTIC ANIMALS

**DANGER - POISON.** Fatal if swallowed or absorbed through skin or inhaled. Corrosive. Causes irreversible eye damage. Causes skin burns. Do not get in eyes, on skin or on clothing. Do not breathe spray mist, vapor or dust. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse.

#### PERSONAL PROTECTION EQUIPMENT (PPE)

Mixers loaders, applicators and other handlers must wear protective clothing (long-sleeved cotton shirt, long pants, shoes plus socks and hat) and gloves (such as nitrile or butyl). Wear protective eyewear such as goggles, face shield or safety glasses. Wear a NIOSH-approved respirator with an organic vapor (OV) cartridge with a combination N, R, or P filter with NIOSH approval number prefix 84A; or NIOSH approved gas mask with an organic vapor canister with NIOSH approval number prefix TC-14G; or a NIOSH approved powered air purifying respirator with organic vapor (OV) cartridge and combination HE filter with NIOSH approval number prefix TC 23C. **User Safety Requirements:** Follow manufacturer's instructions for cleaning / maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Wash the outside of gloves before removing. Discard clothing and other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them.

### USER SAFETY RECOMMENDATIONS

Remove clothing / PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Remove PPE immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the toilet. Remove and wash contaminated clothing before reuse.

### ENVIRONMENTAL HAZARDS

This material is toxic to fish and aquatic invertebrates. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans and other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge.

Do not discharge effluent into sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

### PHYSICAL AND CHEMICAL HAZARDS

Flammable. Keep away from heat and open flame.

FIRST AID	
<b>IF SWALLOWED:</b>	• Immediately call a poison control center or doctor. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give any liquid to the person. • Do not give anything by mouth to an unconscious person.
<b>IF ON SKIN OR CLOTHING:</b>	• Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15 – 20 minutes. • Call a poison control center or doctor for treatment advice.
<b>IF IN EYES:</b>	• Hold eye open and rinse slowly and gently with water for 15-20 minutes. • Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. • Call a poison control center or doctor for treatment advice.
<b>IF INHALED:</b>	• Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
Have the product container or label with you when calling a poison control center or doctor or going for treatment. You may also contact 1-800-222-1222 for emergency medical treatment information.	
For Hazardous Materials [or Dangerous Goods] Incident Spill, Leak, Fire, Exposure, or Accident Call CHEMTREC Day or Night. Within USA and Canada 1-800-424-9300. Outside USA and Canada +1-703-741-5970 CHEMTREC. Account #15570. For Non Emergencies call New Nautical Coatings Inc., Within the USA and Canada 1-800-528-0997, Outside USA and Canada +1-727-523-8053.	
<b>NOTE TO PHYSICIAN:</b> Probable mucosal damage may contraindicate the use of gastric lavage. Contains petroleum distillate, vomiting may cause aspiration pneumonia.	

E.P.A. Registration No. 44891-7 / E.P.A. Establishment No. 44891-FL-1